



SPAWER

Heat pumps for spas



O'SPA

Compact & efficient:
Manages the spa heater

- Operates down to -7°C
- Reversible hot/cold
- Automatic de-icing
- Compatible with all spas
- Control through a wifi connection
- Integrated pilot for an auxiliary circulation pump (relay optional)



Climate
COP air 26°C / water 26°C
Noise level at 10 m (db(A))

5 kW
Temperature
5.2
< 32



Certification:

Oyster

POOLS & HOT TUBS LTD

01291 690 614

WWW.OYSTERPOOLS.CO.UK

Raglan Garden Centre, Raglan, Usk.
Monmouthshire. NP15 2BH.

HEAT PUMP WARRANTY

2
YEARS

COMPRESSOR WARRANTY

5
YEARS

TITANIUM COIL
WARRANTY AGAINST CORROSION

10
YEARS

OPERATES
DOWN TO -7°C

2 CAPACITIES
AVAILABLE 3 AND 5 KW

TECHNICAL DATA

Capacity	3 kW	5 kW
Suggested climate	Hot	Temperate
Air 26°C Capacity (kW)	3	5.02
Water 26°C Power consumption (kW)	0.58	0.97
Hygro 80% COP	5.15	5.2
Air 26°C Capacity (kW)	2	4.03
Water 26°C Power consumption(kW)	0.5	1
Hygro 70% COP	4.01	4.05
Air 35°C Capacity (kW)	1.46	2.99
Water 27°C Power consumption (kW)	0.53	1
Hygro 70% COP	2.75	2.99
Power supply	Mono 220-240V / 50 Hz	
Connections	32 / 38 mm	
Max. power (kW)	0.7	1.35
Max. current (A)	3.11	5.99
Heating temperature range	10°C / 40°C	
Cooling range	8°C / 28° C	
Operating range	-7°C / 43°C	
Flow (m³/h)	1.3	2.16
Refrigerant	R32	
Packaging dimensions (mm)	470 x 400 x 438	
Dimensions (mm)	440 x 380 x 423	
Net/gross weight (kg)	26 / 28	32 / 35
Noise level at 1 m (db(A))	< 50	< 53
Noise level at 4 m (db(A))	< 38	< 40
Noise level at 10 m (db(A))	< 30	< 32
Compressor type	Rotary	
Heat exchanger	Twisted Tech®Titanium	
Operation	Heating / Cooling / Auto	
Load loss (mCE)	1.2	1.2

Ultra compact, the Poolux O'Spa is a heat pump for spas that can **save you up to 75% in energy consumption when heating your spa** compared to a conventional electric heater (at an equivalent power consumption).

The O'Spa can be installed on any type of hot tub and nordic bath in order to take over the electric heater and optimize the increase in temperature inside your spa.

You only need to connect the heat pump and its relay will manage the electric heater initially integrated to the spa.

The O'Spa is available in 2 capacities: 3kW and 5kW to give you the possibility to choose according to your climate: hot or temperate

ULTRA COMPACT



Plug & Play hydraulic connecting kit (optional)



Remote touch screen (optional)



COMPATIBLE WITH THE SPAWER STEPS



2023 Prices

O-SPA heat Pump	£999
Plumbing & Bypass Kit	£150
Installation, cut panels, plumb bypass and insulate	£350
Package Total (Inc Vat)	£1,499